



Varian and Perkin Elmer Reconditioned Ion Pump Controllers

Ion Pump Controllers Reconditioned to Original Specifications

Equivalent OEM/Part #	Pumping Speed	Volts Out	MA	Volts In
Varian / 921-0006	Appendage	+3,300	40	115/230
Varian / 921-0015	Appendage	+3,300	40	115/230
Varian / 921-0014	Multi-Pump (10)	+3,300	40	115/230
Varian / 921-0065	Multi-Pump (10)	+3,300	40	115/230
Varian / 921-0011	8 L/Sec	+3,550	180	115/230
Varian / 921-0018	11 L/Sec (H2O)	+7,200	750	208/230
Varian / 921-0013	15 L/Sec	+7,200	70	115/230
Varian / 921-0012	50 L/Sec	+3,750	350	115/230
Varian / 921-0007	80 L/Sec	+7,200	190	115/230
Varian / 921-0041	110 L/Sec	-5,200	480	115/208/230
Varian / 921-0004	140 L/Sec	+7,200	235	115/230
Varian / 921-0034	140 L/Sec	+7,200	300	115/230
Varian / 921-0043	220 L/Sec	-5,200	800	115/208/230
Varian / 921-0036	270 L/Sec	+7,200	600	115/230
Varian / 921-0045	400 L/Sec	-5,200	1,600	208/230
Varian / 921-0005	500 L/Sec	+7,200	750	208/230
Varian / 921-0038	500 L/Sec	+7,200	1,250	208/230
Varian / 921-0000	1,000 L/Sec	+7,200	2,000	230/460
Varian / 921-0062	8, 20, 30 & 60 L/Sec	+3,300 -5,200	120 200	120/240
Varian / 921-0066	110, 220, 400 L/Sec 140, 270, 500 L/Sec	-5,200 +7,200	675 465	208/240
Perkin Elmer / 60-063	5-25 L/Sec	+4,750	150	115
Perkin Elmer / 222-0410	5-25 L/Sec	+4,750	150	115
Perkin Elmer / 60-104	50 L/Sec	+4,750	350	115
Perkin Elmer / 60-655	50 L/Sec	+4,750	350	115
Perkin Elmer / 222-0510	50 L/Sec	+4,750	350	115
Perkin Elmer / 222-0400	25-270 L/Sec	+/-5,500	220	110/230
Perkin Elmer / 222-0530	60-220 L/Sec	+/-5,500	250	115/208/230
Perkin Elmer / 60-160	100-500 L/Sec	+4,750	1,000	208/230
Perkin Elmer / 222-0600	100-2400 L/Sec	+4,750	1,000	208/230
Perkin Elmer / 224-0635	Boostivac	+5,500	250	117
Perkin Elmer / 222-0630	120-500 L/Sec	+/-7,000	600	208/230