

Stock Seamless Molybdenum Tubing

O.D. (inches)	I.D. (inches)	Wall (inches)	Max. Length
0.020	0.012	0.004	24
0.025	0.015	0.005	24
0.030	0.018	0.006	24
0.035	0.021	0.007	24
0.040	0.024	0.008	24
0.050	0.030	0.010	24
0.060	0.036	0.012	36
0.070	0.042	0.014	36
0.075	0.045	0.015	36
0.080	0.048	0.016	36
0.090	0.054	0.018	48
0.110	0.066	0.022	60
0.125	0.095	0.015	60
	0.074	0.025	60
0.140	0.084	0.028	60
0.156	0.093	0.031	60
0.170	0.102	0.034	60
0.175	0.105	0.035	60
0.187	0.147	0.020	
	0.127	0.030	
	0.112	0.037	60
0.200	0.120	0.040	60
0.218	0.132	0.043	60
0.225	0.135	0.045	50
0.250	0.210	0.020	
	0.190	0.030	
	0.150	0.050	40
0.312	0.252	0.030	
	0.187	0.062	30
0.340	0.206	0.068	20
0.375	0.325	0.025	
	0.295	0.040	
	0.225	0.075	20
0.500	0.440	0.030	
	0.420	0.040	
	0.380	0.060	
0.625	0.525	0.050	
0.750	0.630	0.060	
0.875	0.755	0.060	
1.000	0.940	0.030	

Standard Tolerances:

O.D.	.020 - .124	=	+ .001/- .000
O.D.	.125 - .187	=	+ .002/- .000
O.D.	.188 - 1.000	=	+ .005/- .000
Wall	+/-10% of wall thickness		



- 99.95% Pure
- Random lengths or cut to length.
- Intermediate, special and metric sizes as well as other tolerances or longer lengths available on request.
- Also available, Moly rod, sheet and plate.